

KPM/KLS-35

Optical Power Meter & Optical Light Source




Wavelengths
850~1625nm



Accuracy
0.2dB



Anti-drop
2m



Universal Adaptor
FC/SC/ST



Dynamic Range
80dB

Specifications

| | | |
|-----------------------------|--|--------------------|
| Model | KPM-35 | KLS-35 |
| Wavelength(nm) | 850/1300/1310/1490/1550/1625 | 850/1300/1310/1550 |
| Applicable fiber | SM,MM | SM,MM |
| Detector type | InGaAs | --- |
| Measuring range(dBm) | -70~+10 | --- |
| Uncertainty | 5% | --- |
| Output Power(dBm) | --- | -5 |
| Connector type | 2.5mm universal port +FC,SC,LC adaptor | |
| Working temperature(°C) | -10 to +60 | |
| Storage temperature(°C) | -70~+60 | |
| Battery | Alkaline Battery (3AA 1.5V batteries) | |
| Continuous working time (h) | 240 | 45 |
| Dimensions(mm) | 160(L)x85(W)x45(H) | |
| Weight(g) | 220 | |

Product Configuration

| | |
|---|---------------|
| 1 | Packing box |
| 2 | Packing bag |
| 3 | Machine |
| 4 | Certificate |
| 5 | Warranty card |
| 6 | FC connector |
| 7 | Instructions |

